

Serial Number: 09/389,085

REMARKS

Favorable reconsideration of this application as presently amended is respectfully requested. Claims 1, 2, 4-10, 12-15 and 17-27 are pending. Claims 3 and 16 are canceled, claims 1 and 14 are amended and claims 23-27 are added.

The Examiner is thanked for indicating that claims 21 and 22 are allowed. The Examiner is thanked for indicating that claims 4, 5, 8-10 and 17-18 would be allowable if rewritten in independent format including all of the limitations of the base claim and any intervening claims, in order to overcome the objection of their being dependant upon a rejected base claim.

Claims 3 and 16 are rejected under 35 U.S.C. § 112, second paragraph. This rejection has been obviated by the amendments to the claims.


Claims 1-2, 6-7, 13-15 and 20 are rejected under 35 U.S.C. § 103(a) as being unpatentable over U.S. Patent No. 6,031,919 to Funahashi *et al.* in view of U.S. Patent No. 5,327,504 to Hobelsberger. This rejection has been obviated by the amendments to the claims.

Claims 12 and 19 are rejected under 35 U.S.C. § 103(a) as being unpatentable over U.S. Patent No. 6,031,919 to Funahashi *et al.* in view of U.S. Patent No. 5,327,504 to Hobelsberger and further in view of U.S. Patent No. 5,693,917 to Bertagni *et al.* This rejection has been obviated by the amendments to the claims.

Serial Number: 09/389,085

If the Examiner has any questions or concerns regarding the present response, the Examiner is invited to contact Steven J. Prewitt at 703-591-2664. In view of the foregoing, it is respectfully submitted that this application is in condition for allowance, and favorable action is respectfully solicited.

Respectfully submitted,

A handwritten signature in black ink, appearing to read "Steven J. Prewitt", written over a horizontal line.

Steven J. Prewitt
Reg. No. 45,023

Jagtiani + Gutttag
Democracy Square Business Center
10379-B Democracy Lane
Fairfax, Virginia 22030
703-591-2664

December 12, 2002



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)	
)	
MULLINS, Joe H.)	Examiner: GRIER, Laura A.
)	
Serial Number: 09/389,085)	Art Unit: 2644
)	
Filed: September 2, 1999)	
)	
For: LOW FREQUENCY FEEDBACK)	Docket No.: UNME-0019-1
CONTROLLED AUDIO SYSTEM)	

Director of the U.S. Patent and Trademark Office
Washington, D.C. 20231

VERSION WITH MARKINGS TO SHOW CHANGES MADE

RECEIVED

DEC 13 2002

Technology Center 2600

Sir:

Below are the amendments in the accompanying Amendment for the above-identified application shown in redlined format:

IN THE CLAIMS

Please cancel claims 3 and 16 without prejudice or disclaimer.

Please amend the claims, without prejudice or disclaimer, as indicated below:

1. ~~(Twice Amended)~~ An audio system, comprising:
 - a cabinet having an opening in a first wall thereof;
 - a first speaker for emitting audio output, said first speaker being mounted inversely at said opening of said cabinet;
 - a passive radiator for emitting audio output, said passive radiator mounted in said cabinet opposite said first speaker; and
 - a sensor for sensing pressure caused by the audio output from said first speaker, said sensor being mounted in said cabinet by a sensor mounting structure

Serial Number: 09/389,085

joined to said cabinet, said sensor mounted in such a manner as to receive a signal from both the speaker and the passive radiator, wherein said sensor is a speaker.

2. The audio system of claim 1, wherein said audio system comprises a low frequency audio system.

4. The audio system of claim 1, wherein said sensor mounting structure comprises a damped elastic mounting structure.

5. The audio system of claim 1, wherein said sensor mounting structure comprises an enclosure mounted on said first wall and including said opening in said first wall.

6. The audio system of claim 1, further comprising a means for adjusting the audio output of said first speaker based on said pressure sensed by said sensor.

7. The audio system of claim 1, wherein said first speaker has a speaker maximum width and said sensor has a sensor maximum width, and said sensor maximum width is smaller than said speaker maximum width.

8. The audio system of claim 1, wherein said sensor has a signal-to-noise ratio of at least of 100 dB.

9. The audio system of claim 1, wherein said audio system has a feedback factor of 30 to 50 dB when said first speaker operates at a frequency of about 15 to 300 Hz.

10. The audio system of claim 1, further comprising acoustic absorbing material contained in said cabinet.

12. The audio system of claim 1, wherein said first speaker comprises an electrodynamic planar speaker.

Serial Number: 09/389,085

13. The audio system of claim 1, wherein said first speaker comprises an electrostatic planar speaker.

14. ~~(Twice Amended)~~ A method for improving acoustical accuracy in an audio system comprising the steps of:

mounting a first speaker inversely in an opening of a wall of a cabinet;

mounting a passive radiator in said cabinet opposite said first speaker;

sensing pressure from audio output from the first speaker and the passive radiator; and

adjusting the audio output from the first speaker based on the pressure sensed in said sensing step, ~~wherein said sensing step is performed by a sensor comprising a speaker.~~

15. The method of claim 14, wherein the audio system comprises a low frequency audio system.

17. The method of claim 14, wherein said sensing step is performed by a sensor having a signal-to-noise ratio of at least of 100 dB.

18. The method of claim 14, wherein said method produces an audio system feedback factor of 30 to 50 dB when the first speaker operates at a frequency of about 15 to 300 Hz.

19. The method of claim 14, wherein said first speaker comprises an electrodynamic planar speaker.

20. The method of claim 14, wherein said first speaker comprises an electrostatic planar speaker.

21. An audio system, comprising:

Serial Number: 09/389,085

a cabinet having an opening in a first wall thereof;
a first speaker for emitting audio output, said first speaker being mounted inversely at said opening of said cabinet; and
a sensor for sensing pressure caused by the audio output from said first speaker, said sensor being mounted in said cabinet by a sensor mounting structure joined to said cabinet, wherein said sensor mounting structure comprises a damped elastic mounting structure.

22. An audio system, comprising:

a cabinet having an opening in a first wall thereof;
a first speaker for emitting audio output, said first speaker being mounted inversely at said opening of said cabinet; and
a sensor for sensing pressure caused by the audio output from said first speaker, said sensor being mounted in said cabinet by a sensor mounting structure joined to said cabinet, wherein said sensor mounting structure comprises an enclosure mounted on said first wall and including said opening in said first wall.

Please add new claims 23-27 as follow:

23. (New) An audio system, comprising:

a cabinet having an opening in a first wall thereof;
a first speaker for emitting audio output, said first speaker being mounted inversely at said opening of said cabinet;
a passive radiator for emitting audio output, said passive radiator mounted in said cabinet opposite said first speaker; and
a sensor for sensing pressure caused by the audio output from said first speaker, said sensor being mounted in said cabinet by a sensor mounting structure joined to said cabinet, said sensor mounted in such a manner as to receive a signal from both the speaker and the passive radiator, wherein said sensor has a signal-to-noise ratio of at least of 100 dB.

Serial Number: 09/389,085

24. (New) An audio system, comprising:
- a cabinet having an opening in a first wall thereof;
 - a first speaker for emitting audio output, said first speaker being mounted inversely at said opening of said cabinet;
 - a passive radiator for emitting audio output, said passive radiator mounted in said cabinet opposite said first speaker; and
 - a sensor for sensing pressure caused by the audio output from said first speaker, said sensor being mounted in said cabinet by a sensor mounting structure joined to said cabinet, said sensor mounted in such a manner as to receive a signal from both the speaker and the passive radiator, wherein said audio system has a feedback factor of 30 to 50 dB when said first speaker operates at a frequency of about 15 to 300 Hz.
25. (New) An audio system, comprising:
- a cabinet having an opening in a first wall thereof;
 - a first speaker for emitting audio output, said first speaker being mounted inversely at said opening of said cabinet;
 - a passive radiator for emitting audio output, said passive radiator mounted in said cabinet opposite said first speaker;
 - a sensor for sensing pressure caused by the audio output from said first speaker, said sensor being mounted in said cabinet by a sensor mounting structure joined to said cabinet, said sensor mounted in such a manner as to receive a signal from both the speaker and the passive radiator; and
 - acoustic absorbing material contained in said cabinet.
26. (New) A method for improving acoustical accuracy in an audio system comprising the steps of:
- mounting a first speaker inversely in an opening of a wall of a cabinet;
 - mounting a passive radiator in said cabinet opposite said first speaker;
 - sensing pressure from audio output from the first speaker and the passive radiator; and

Serial Number: 09/389,085

adjusting the audio output from the first speaker based on the pressure sensed in said sensing step, wherein said sensing step is performed by a sensor having a signal-to-noise ratio of at least of 100 dB.

27. (New) A method for improving acoustical accuracy in an audio system comprising the steps of:

mounting a first speaker inversely in an opening of a wall of a cabinet;

mounting a passive radiator in said cabinet opposite said first speaker;

sensing pressure from audio output from the first speaker and the passive radiator; and

adjusting the audio output from the first speaker based on the pressure sensed in said sensing step, wherein said method produces an audio system feedback factor of 30 to 50 dB when the first speaker operates at a frequency of about 15 to 300 Hz.